



### General Description:

The EX-LITE BL series are LED bollards with the latest CCT and wattage selecting technology. It has three different wattages and CCTs all in one bollard.

### Construction:

- Corrosion resistant polyester powder coat finish, available in custom colors.
- Cast aluminum structure that resists high shock and vibration.

### Electrical:

- Wattage selectable from 12W, 16W & 22W.
- High Power Factor, low THD UL listed driver with 10KV surge protection.
- Universal line voltage input 120-277V, 347/480V optional
- 0-10V dimmable

### Optical:

- Ultra wide beam light distribution
- CCT selectable from 30K, 40K & 50K

### Warranty:

- 5 years' warranty for complete fixture

### Listings:

- ETL
- FCC
- DLC
- IP65



### Ordering Information:

Family Model	Style	Wattage	CCT	Finish Color	Control	Input Voltage
BLRD	CY=Crystal Head	12W=12W	50K=5000K	(blank)=Bronze, Std	(blank)=None, Std	(blank)=110/277V, Std
	LV=Louver Head	16W=16W	40K=4000K	WH=White	PCB=Button Photocell	HV=480V
		22W=22W	30K=3000K	GR=Gray		
				BL=Black		

PROJECT NAME: \_\_\_\_\_ CATALOG NUMBER: \_\_\_\_\_

NOTES: \_\_\_\_\_ FIXTURE TYPE: \_\_\_\_\_

### Specs:

Style	Wattage	Lumens	CCT	Height	OD
Crystal Head	12W	1,440lm	3000K/4000K/5000K	42"	6.3"
Louver Head	16W	1,920lm	3000K/4000K/5000K	42"	6.3"
	22W	2,640lm	3000K/4000K/5000K	42"	6.3"

### Photometrics:

